










XS4 Original+ for EURO mortise locks & tubular latches




The Salto XS4 Original+ narrow body version is designed to fit most European profile doors and mortise locks standards. Easy to install and retrofit, it can replace your existing door hardware and fits any door with a broad range of different models and functions. The XS4 Original+ incorporates the latest BLUEnet wireless and mobile credentials technology to accommodate access control needs of both today and tomorrow.

E i 4xx series





 **SALTO recommends the use of a mortise lock, with a maximum 4° pre-turn.**

SALTO recommande d'utiliser des serrures à mortaiser avec un angle au repos de 4° maximum.

SALTO recomienda utilizar cerraduras con un pregiro máximo de 4°.

초기 최대 4° 프리턴. SALTO는 사전 회전이 최대 4°인 모티스락의 사용을 권장합니다. SALTO建議使用暗鎖, 最大預轉角度為4°。

SALTO Tubular latch


 **To be used only with SALTO compatible escutcheons!**

A utiliser uniquement avec les ensembles plaques-béquilles SALTO compatibles!

¡Utilizar solamente con escudos SALTO compatibles!

SALTO 호환 에스커천에만 사용!


僅適用於與SALTO相容的護板！




i

	t Door thickness		
3	32 - 47mm	35 mm	-
4	45 - 60 mm	50 mm	-
6	60 - 75 mm	30 mm	x2
7	75 - 90 mm	45 mm	x2
9	90 - 105 mm	30 mm	x4
1	105 - 120 mm	45 mm	x4
2	32 - 53 mm	35 mm	-
A		35 mm	-
B		45 mm	-
5		45 mm	-


1




2




3



4



5



Eng Installation



F Installation

E Instalación


KR 설치

Zh 安裝


1




2




3




4




5




6




7




8




9



10




11



	t	
	Door thickness	
3	32 - 47mm	35 mm
4	45 - 60 mm	50 mm
6	60 - 75 mm	30 mm
7	75 - 90 mm	45 mm
9	90 - 105 mm	30 mm
1	105 - 120 mm	45 mm
2	32 - 53 mm	35 mm
A		35 mm
B		45 mm
5		45 mm

12



(*) NOTE: Distance 7F on models 56 - 57 - 66 and P6 does not permit to use of the self-drilling screw to improve the escutcheon vertical alignment.

(*) NOTA: La distancia 7F en modelos 56 - 57 - 66 y P6 no permite utilizar el tornillo que mejora el alineamiento vertical del escudo.

(*) HINWEIS: Bei Abstand 7F der Modelle 56,57,66 und P6 ist die Verwendung der selbstschneidenden Schraube zur Verbesserung der vertikalen Ausrichtung des Beschlags nicht erlaubt.

(*) REMARQUE: La distance de 7F sur les modèles 56 - 57 - 66 et P6 ne permet pas d'utiliser la vis auto-foreuse pour améliorer l'alignement vertical de l'ensemble plaques béquilles.


(*) NOTA: la distanza 7F su i modelli 56 - 57 - 66 e P6 non consente l'uso della vite autoforante per migliorare l'allineamento verticale della placca.

(*) NOTA: A distância 7F nos modelos 56 - 57 - 66 e P6 não permite a utilização do parafuso auto-perfurante para melhorar o alinhamento vertical do escudo.


(*) 참고: 모델 56 - 57 - 66 및 P6 의 거리 7F 는 에스커션 수직 정렬을 개선하기 위해 자체 드릴링 나사를 사용할 수 없습니다.

(*) 注意: 在型號 56 - 57 - 66 及 P6 上, 距離 7F 不允許使用自鑽螺絲來改善護板的垂直對齊。


13




14



15



16



**AT THIS POINT DO NOT
CLOSE THE DOOR
PROGRAM THE LOCK
FIRST**

**NO CIERRE LA PUERTA.
PROGRAMME LA CERRADURA**

**TÜRE NICHT SCHLIESSEN.
ZUERST SCHLOSS
PROGRAMMIEREN**

**NE FERMEZ PAS LA PORTE.
PROGRAMMEZ LA BÉQUILLE
AVANT**



**PRIMA DI CHIUDERE LA
PORTA, PROGRAMARE LA
SERRATURA**

**NESTE PONTO NÃO
FECHE A PORTA.
PROGEME O ESCUDO
PRIMEIRO**


**이때 문을 닫지 말고 먼저 잠금
장치를 프로그래밍하십시오.**

**此時請勿
關閉門扇
請先設定門鎖程式**

Eng Battery change F Remplacer les piles E Cambio de pilas KR 배터리 교체 Zh 電池更換 **LR03**



Ei451 xx
Ei461 xx



Eng HOTEL GUEST ROOM LOCK


- (E) HABITACION HOTEL
- (D) HOTELZIMMERSCHLOSS
- (F) PIÈCE D'HÔTEL
- (I) CAMERE HOTEL
- (P) QUARTO DE HOTEL
- (KR) 호텔 객실 잠금
- (Zh) 飯店客房門鎖 飯店客房門鎖

(Zh) *僅適用於厚度超過60毫米[2-3/8 英寸]的門

(KR) * 두께가 60mm(2-3/8")를 초과하는 문에만 필요

(E) * Sólo para puertas de espesor mayor de 60mm [2-3/8"]

(Eng) * Required only for doors that exceed 60mm [2-3/8"] thickness



E T4xx.. series

